














CONTAINER EQUIPMENT

							
Size	20'x 8'x 8'6"	20'x 8'x 8'6"	20'x 8'x 8'6"	20'x 8'x 8'6"	20'x 8'x 8'6"	20'x 8'x 8'6"	20'x 8'x 8'6"
Equipment-Type	RF Integrated Reefer Container	IH Integrated Reefer Hanging Cargo	DC/DV Dry Cargo Container	VT Top Vented**	OT Open Top Container	FR Flat Rack Collapsible	
Interior Dimensions (Length, Width, Height)	5,558 mm (L) 2,300 mm (W) 2,324 mm (H)	5,555 mm (L) 2,294 mm (W) 2,291 mm (H)	5,906 mm (L) 2,352 mm (W) 2,396 mm (H)	5,898 mm (L) 2,344 mm (W) 2,396 mm (H)	5,898 mm (L) 2,333 mm (W) 2,348 mm (H)	5,929 mm (L) 1,980 mm (W) 2,270 mm (H)	
Door Opening (Width, Height)	2,290 mm (W) 2,290 mm (H)	2,290 mm (W) 2,290 mm (H)	2,338 mm (W) 2,283 mm (H)	2,338 mm (W) 2,273 mm (H)	2,292 mm (W) 2,280 mm (H)	- -	
Weights Gross Tare Payload	24,000 kg / 30,480 kg* 2,990 kg / 3,050 kg* 21,010 kg / 27,430*	30,480 kg 3,522 kg 28,958 kg	24,000 kg / 30,480 kg* 2,237 kg / 2,340 kg* 21,763 kg / 28,140 kg*	24,000 kg 2,400 kg 21,600 kg	22,773 kg / 30,480 kg* 2,337 kg / 2,290 kg* 20,436 kg / 28,190 kg*	30,000 kg / 40,000 kg* 2,600 kg / 2,800 kg* 27,400 kg / 37,200 kg*	
Volume	30.00 cbm	29,20 cbm	33,29 cbm / 32 cbm	33,12 cbm	32,31 cbm	-	
							
Size	40'x 8'x 9'6"	40'x 8'x 9'6"	40'x 8'x 8'6"	40'x 8'x 8'6"	40'x 8'x 9'6"	40'x 8'x 8'6"	40'x 8'x 9'6"
Equipment-Type	RH Integrated Reefer High Cube Container	HC Dry Cargo High Cube Container	DC/DV Dry Cargo Container	OT Open Top Container	OH Open Top High Cube Container	FR Flat Rack Collapsible	FH/HC Flat Rack Collapsible
Interior Dimensions (Length, Width, Height)	11,582 / 11,651 mm (L) 2,296 / 2,310 mm (W) 2,552 / 2,607 mm (H)	12,033 mm (L) 2,352 mm (W) 2,698 mm (H)	12,030 mm (H) 2,347 mm (W) 2,393 mm (H)	12,040 mm (L) 2,320 mm (H) 2,290 mm (H)	12,032 mm (L) 2,350 mm (W) 2,655 mm (H)	12,072 mm (L) 2,286 mm (W) 1,978 mm (H)	12,054 mm (L) 2,380 mm (W) 2,260 mm (H)
Door Opening (Width, Height)	2,288 / 2,310 mm (W) 2,490 / 2,576 mm (H)	2,340 mm (W) 2,586 mm (H)	2,338 mm (W) 2,283 mm (H)	2,320 mm (H) 2,270 mm (H)	2,338 mm (W) 2,582 mm (H)	- -	- -
Weights Gross Tare Payload	34,800 kg 4,260 / 4,900 kg 29,900 / 30,330 kg	32,500 kg 4,000 kg 28,500 kg	32,500 kg 3,800 kg 28,700 kg	30,480 kg 4,200 kg 26,280 kg	32,500 kg 4,300 kg 28,200 kg	45,000 kg 5,180 kg 39,820 kg	45,000 kg 5,500 kg 39,500 kg
Volume	68.6/70 cbm	76.37 cbm	67.34 cbm	63.97 cbm	75.10 cbm	-	-

* Various 20 ft equipment types are available in above mentioned range.

** With 16 ventilations each side panel Top.